

# Random Context Grammars

Jiří Techet    Tomáš Masopust    (Alexander Meduna)

Department of Information Systems  
Faculty of Information Technology  
Brno University of Technology  
Božetěchova 2, Brno 61266, Czech Republic

Modern Formal Language Theory, 2007

# Random Context Grammar

## Random Context Grammar

A (permitting) **random context grammar** is a pair

$$H = (G, R)$$

where

- $G = (N, T, P, S)$  is a context-free grammar
- $R$  is a finite relation from  $P$  to  $N$

## Notation

If  $p : A \rightarrow x \in P$ ,  $R(p) = Q$ , we write

$$(p : A \rightarrow x, Q)$$

where  $Q \subseteq N$  is called a **permitting context**

# Derivation Step of Random Context Grammar

## Derivation Step

For  $x, y \in V^*$ ,  $p \in P$ ,

$$x \Rightarrow y [p] \text{ in } H$$

if

1  $x \Rightarrow y [p] \text{ in } G$  and

2  $R(p) \subseteq \text{alph}(x)$

# Random Context Grammar with Appearance Checking

## Random Context Grammar with Appearance Checking

A **random context grammar with appearance checking** is a triple

$$H = (G, R, F)$$

where

- $G = (N, T, P, S)$  is a context-free grammar
- $R, F$  are two finite relations from  $P$  to  $N$

## Notation

If  $p : A \rightarrow x \in P$ ,  $R(p) = Q$ , and  $F(p) = K$ , we write

$$(p : A \rightarrow x, Q, K)$$

where  $Q$  and  $K$  are **permitting** and **forbidding contexts**, respectively

# Derivation Step of Random Context Grammar with Appearance Checking

## Forbidding Grammar

If every  $(p : A \rightarrow x, Q, K)$  satisfies  $Q = \emptyset$ , then  $H$  is called a **forbidding grammar**.

## Derivation Step

For  $x, y \in V^*$ ,  $p \in P$ ,

$$x \Rightarrow y [p] \text{ in } H$$

if

- 1  $x \Rightarrow y [p] \text{ in } G$
- 2  $R(p) \subseteq \text{alph}(x)$
- 3  $F(p) \cap \text{alph}(x) = \emptyset$

# Example – Permitting Grammar I

## Example

1  $(S \rightarrow ABC, \emptyset)$

2  $(A \rightarrow aA', \{B\})$

$(B \rightarrow bB', \{C\})$

$(C \rightarrow cC', \{A'\})$

3  $(A' \rightarrow A, \{B'\})$


$(B' \rightarrow B, \{C'\})$

$(C' \rightarrow C, \{A\})$

4  $(A \rightarrow a, \{B\})$

$(B \rightarrow b, \{C\})$

$(C \rightarrow c, \emptyset)$



# Example – Permitting Grammar II

## Example


$$\begin{aligned} S &\Rightarrow ABC && 1 \\ &\Rightarrow^3 aA'bB'cC' && 2 \\ &\Rightarrow^3 aAbBcC && 3 \\ &\Rightarrow^3 aaA'bbB'ccC' && 2 \\ &\Rightarrow^3 aaAbbBccC && 3 \\ &\vdots \\ &\Rightarrow^3 a^n Ab^n Bc^n C && 3 \\ &\Rightarrow^3 a^{n+1} b^{n+1} c^{n+1} && 4 \end{aligned}$$

$$L(H) = \{a^k b^k c^k : k \geq 1\}$$

# Example – Forbidding Grammar I

## Example

- (1 :  $S \rightarrow AA, \emptyset, \{B, D\}$ )
- (2 :  $A \rightarrow B, \emptyset, \{S, D\}$ )
- (3 :  $B \rightarrow S, \emptyset, \{A, D\}$ )
- (4 :  $A \rightarrow D, \emptyset, \{S, B\}$ )
- (5 :  $D \rightarrow a, \emptyset, \{S, A, B\}$ )





# Example – Forbidding Grammar II

## Example

		rules
$S \Rightarrow$	$AA$	1
$\Rightarrow^2$	$BB$	2
$\Rightarrow^2$	$SS$	3
$\Rightarrow^2$	$AAAA$	1
$\Rightarrow^4$	$BBBB$	2
$\Rightarrow^4$	$SSSS$	3
	$\vdots$	
$\Rightarrow^{2^i}$	$A^{2^{i+1}}$	1
$\Rightarrow^{2^{i+1}}$	$D^{2^{i+1}}$	4
$\Rightarrow^{2^{i+1}}$	$a^{2^{i+1}}$	5

$$L(H) = \{a^{2^n} : n \geq 1\}$$



J. Dassow and Gh. Păun.

*Regulated Rewriting in Formal Language Theory.*

Akademie-Verlag, Berlin, 1989.



A. P. J. van der Walt.

Random context grammars.

In *Proceedings of Symposium on Formal Languages*, 1970.